

YOL VERME İÇİN TEKNİK VERİLER												
MOTOR					SİGORTA		KANTAKTÖR				TERMİK ROLE	
GÜÇÜ		COSQ	VERİM	AKIM	DİREK	YILDIZ ÜÇGEN	DİREK	YILDIZ/ÜÇGEN			DİREK	YILDIZ ÜÇGEN
KW	HP							N	ÜÇGEN	YILDIZ		
0.25	0.34	0.7	52	0.8	2	-	9	-	-	-	0.63-1	-
0.37	0.5	0.72	64	1.2	4	-	9	-	-	-	1-1.6	-
0.55	0.75	0.75	69	1.6	4	-	9	-	-	-	1-1.6	-
0.75	1	0.8	74	2	6	-	9	-	-	-	1.6-2.5	-
1.1	1.5	0.83	77	2.8	6	-	9	-	-	-	2.5-4	-
1.5	2	0.83	76	3.7	10	-	9	-	-	-	2.5-4	-
2.2	3	0.83	81	5.2	10	-	9	-	-	-	4-6.3	-
3	4	0.84	81	6.8	16	-	16	-	-	-	6.3-10	-
4	5.5	0.84	82	8.6	20	-	16	-	-	-	6.3-10	-
5.5	7.5	0.85	83	11.5	25	20	16	16	16	16	10-16	6.3-10
7.5	10	0.85	85	15	35	25	32	16	16	16	10-16	6.3-10
11	15	0.86	87	22.5	35	35	32	32	32	16	16-25	10-16
15	20	0.86	87	30	50	35	45	32	32	16	25-40	16-25
18.5	25	0.86	88	36	63	50	45	32	32	16	25-40	16-25
22	30	0.87	89	42	63	63	63	32	32	16	40-63	16-25
30	40	0.87	90	57	80	63	63	45	45	32	40-63	25-40
37	50	0.87	90	71	100	80	100	63	63	45	55-80	40-53
45	60	0.88	91	86	125	100	110	63	63	45	70-100	40-53
55	75	0.88	91	103	160	125	170	110	110	63	100-135	53-63
75	100	0.88	91	140	200	160	170	170	170	110	130-160	70-100
90	120	0.88	92	168	225	200	250	170	170	110	150-170	70-100

YILDIZ ÜÇGEN DEVREDE
KUMANDA
KONTAK İHTİYACI

K1 2NO
K2 1NC
K3 1NO+1NC